



CARGADOR USB 65W GaN

Quickcharge 3.0 + Power Delivery



Potencia máxima	65W
Conectores	- 2 x USB-C - 1 x USB-A
Entrada	- Voltaje: 100VAC ~ 240VAC (50 ~ 60Hz) - Intensidad: 1.5A
Salida	- USB-C1/C2 (65W): 5VDC @ 3A, 9VDC @ 3A, 12VDC @ 3A, 15VDC @ 3A, 20VDC @ 3.25A, 3.3~16VDC @ 3.25A, 3.3~21VDC @ 3A - USB-A (36W): 5VDC @ 3A, 9VDC @ 3A, 12VDC @ 3A - USB-C1 + USB-C2 (45W + 20W): - USB-C1 (45W): 5VDC @ 3A, 9VDC @ 3A, 12VDC @ 3A, 15VDC @ 3A, 20VDC @ 2.25A, 3.3~16VDC @ 2.8A, 3.3~21V @ 2.1A - USB-C2 (20W): 5VDC @ 3A, 9VDC @ 2.22A, 12VDC @ 1.67A - USB-C1/C2 + USB-A (45W + 20W): - USB-C1/C2 (45W): 5VDC @ 3A, 9VDC @ 3A, 12VDC @ 3A, 15VDC @ 3A, 20VDC @ 2.25A, 3.3~16VDC @ 2.8A, 3.3~21V @ 2.1A - USB-A (20W): 5VDC @ 4A - USB-C1 + USB-C2 + USB-A (45W + 20W): - USB-C1 (45W): 5VDC @ 3A, 9VDC @ 3A, 12VDC @ 3A, 15VDC @ 3A, 20VDC @ 2.25A, 3.3~16VDC @ 2.8A, 3.3~21V @ 2.1A - USB-C2 + USB-A (20W): 5VDC @ 4A
Extras	- Protección: Frente a cortocircuito y sobrecarga - Tecnología GaN para una mayor eficiencia y menor calentamiento - Carga rápida PowerDelivery
Peso	133 gr
Part Number	COO-CUP-65CCA
EAN	8437012429970